



FEATURES & BENEFITS

 reliable mounting to enclosure or wall with screw

 for indoor use

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA

Material polyamide 6.6


Halogen-free yes

Operating temperature [°C] -40 ÷ +85

Colour transparent

CERTIFICATES & STANDARDS

Flammability class UL 94 V2



Type	Index Ergom	A	D	d	E	W
EE31 (100 PCS)	E01EM-01040100101	9,5	2,8	4,4	1,2	9,5
EE47 (100 PCS)	E01EM-01040100201	10,3	4,6	4,4	1,2	9,5
EE63 (100 PCS)	E01EM-01040100301	11,1	5,6	4,4	1,2	9,5
EE79 (100 PCS)	E01EM-01040100401	11,9	7,4	4,4	1,2	9,5
EE95 (100 PCS)	E01EM-01040100501	12,7	10,0	4,4	1,2	9,5
EE127 (100 PCS)	E01EM-01040100601	14,3	11,9	4,4	1,2	9,5
EE142 (100 PCS)	E01EM-01040100701	15,1	13,5	4,4	1,2	9,5
EE190 (100 PCS)	E01EM-01040100801	17,5	16,8	4,4	1,5	12,7
EE222 (100 PCS)	E01EM-01040100901	19	21,9	5,1	1,5	12,7
EE285 (100 PCS)	E01EM-01040101001	23	25,0	5,1	1,5	12,7

