

Female piggyback push-on connectors, NW type

FEATURES & BENEFITS



female push-on connector with male push-on connector, as per DIN, with galvanic tin plating, for manual installation

LOGISTIC DATA

Quantity in package [pcs] 100


MECHANICAL DATA

Material brass

Covering tin-plated

DIMENSIONS

s 0,37



ERC

| Type | Index Ergom | Cross-section [mm ²] | Size | DIN | L ₁ | L ₂ | L ₃ | a ₁ | a ₂ | w ₁ | w ₂ | Weight [kg] |
|--------------------------|-------------------|----------------------------------|-----------|-----|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-------------|
| NW 4,8-1/0,8 (100 PCS) | E10KN-01030100100 | 0,5±1 | 4,8 x 0,8 | – | 16 | 6,0 | 6,0 | 6,6 | 3,5 | 3,0 | 4,5 | 0,07 |
| NW 6,3-1/0,8 (100 PCS) | E10KN-01030100301 | 0,5±1 | 6,3 x 0,8 | √ | 20 | 7,4 | 9,0 | 8,8 | 4,3 | 3,0 | 4,5 | 0,12 |
| NW 6,3-2,5/0,8 (100 PCS) | E10KN-01030100400 | 1,5±2,5 | | | | | | | | 3,8 | 5,5 | |