




Insulated male push-on connectors in heat-shrink insulation, WIT type

FEATURES & BENEFITS

-  male push-on connector with heat-shrink insulating sleeve with adhesive, with long Cu tube inside, for double crimping
-  heat-shrink insulation; enhances resistance to vibrations, mitigates short-circuit risk
-  sleeve colours facilitate cross-section identification

LOGISTIC DATA

Quantity in package [pcs]	100
---------------------------	-----

MECHANICAL DATA

Insulation	heat-shrink sleeve
Material	brass
Covering	tin-plated
Operating temperature [°C]	-55 ÷ +125
Shrink temperature [°C]	+60 ÷ +100
Size	6,3x0,8

DIMENSIONS

L ₂	8,0
----------------	-----



Type	Index Ergom	Cross-section [mm ²]	Insulation colour	d	D	L ₁	L ₃	Weight [kg]
WIT 6,3-1/0,8 (100 PCS)	E09KO-02070500201	1	red	1,7	4,8	31,0	21,0	0,08
WIT 6,3-2,5/0,8 (100 PCS)	E09KO-02070500301	2,5	blue	2,3	5,8	31,0	21,0	0,09
WIT 6,3-6/0,8 (100 PCS)	E09KO-02070500401	6	yellow	3,4	6,8	35,0	25,0	0,11